

R10L100-SPT269

10.4" IP69K Stainless PCAP Chassis Display



KEY FEATURES

- 10.4", 1024 x 768, PCAP touch with flat design
- Full IP69K waterproof enclosure, good corrosion resistance
- SUS 316/ AISI 316 stainless steel for food and chemical industries
- Support VESA / YOKE mount



SPECIFICATIONS

Display	
Resolution	1024x768
Contrast Ratio	1000:1
Display Color	16.2M Colors
Touch / Glass	Projected Capacitive Multi Touch Screen
Size	10.4 inches
Panel Brightness	350 nits
View Angles	88,88,88,88
Mechanical	
Dimension	289 x 246 x 49.9 mm
Enclosure	Stainless Housing
Mounting	VESA Mount Yoke Mount
Cooling System	Fanless design
Environment	
Operating Humidity	10% to 90% (non-condensing)
Storage Temperature	-20~60°C
Operating Temperature	0~45°C
IP rating	IP69K
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1 x M12 waterproof connector for touch screen control
Video	1x M12 type connector for VGA input 1x waterproof DVI input (Optional) 1x M21 type connector for HDMI input (Optional)
Indicator	1 x LED Indicator for power 1 x LED Indicator for status
Control	
Button	1 x Power Button 1 x Adjust up button 1 x Adjust down button 1 x ESC (Auto) button 1 x OK (Menu) button
Accessory	
Accessory	100~240V AC to DC Adapter with waterproof connector Power Cord External USB cable with waterproof connector for touchscreen control External VGA cable with waterproof connector
Optional Accessory	External HDMI cable with waterproof connector (Optional) External DVI cable with waterproof connector (Optional)

Waterproof caps
Manual
VESA screws

Power

Power Rating 12V DC (M12 type)

DIMENSIONS UNIT:MM

